

WESTAD SCORPIO 2X

Double Eccentric High Performance Butterfly Valve

DESIGNED FOR FULL SHUT-OFF AND THROTTLING SERVICES.

SCORPIO 2X™ is a high-performance butterfly valve platform engineered for demanding marine, offshore and process applications. Configured to meet the specific requirements of each installation, it delivers reliable shut-off performance, simplified maintenance and long service life across a wide range of operating condition

WESTAD SCORPIO 2X™ fulfills
NORSOK L-001 requirements



Specifications

Temp. range	+180°C to -110°C
Pressure rating	ANSI Class 150/300, ISO PN 10/16/25/40
Size range	DN 80 - 1000 (3" - 40") Other sizes on request
Services	For tight shut-off and throttling services
End to end	Wafer: API 609 Cat. B table 3A. ASME B16.47 Series A>24" Lug: API 609 Cat. B table 3A. ASME B16.47 Series A>24" Double flanged: ISO 5752
End connection	ISO PN 10/16/20/25/40/50 JIS 10k/16k ANSI Class 150/300



PROVEN TECHNOLOGY

After more than 120 years of valve manufacturing, KLINGER Westad has designed a valve for special applications that will perform under extreme conditions.

Materials Duplex, Super duplex, SS 316,

Contact information



KIM ARILD TANDBERG

Commercial director
kat@klinger-westad.com
+47 474 59 002

Other

Project sales: sales@klinger-westad.com
Spare parts: spareparts@klinger-westad.com
Service: service@klinger-westad.com