KLINGER Westad

WESTAD SCORPIO 2X

Double Eccentric High Performance Butterfly Valve

DESIGNED FOR FULL SHUT-OFF AND THROTTLING SERVICES.

SCORPIO 2X™ is a high-performance butterfly valve platform engineered for demanding marine, offshore and process applications. Configured to meet the specific requirements of each installation, it delivers reliable shut-off performance, simplified maintenance and long service life across a wide range of operating condition

WESTAD SCORPIO 2X™ fulfills NORSOK L-001 requirements



Specifications

Temp. range	+180°C to -110°C
Pressure rating	ANSI Class 150/300, ISO PN 10/16/25/40
Size range	DN 80 - 1000 (3” - 40”) Other sizes on request
Services	For tight shut-off and throttling services
End to end	Wafer: API 609 Cat. B table 3A. ASME B16.47 Series A>24” Lug: API 609 Cat. B table 3A. ASME B16.47 Series A>24” Double flanged: ISO 5752
End connection	ISO PN 10/16/20/25/40/50 JIS 10k/16k ANSI Class 150/300
Materials	Duplex, Super duplex, SS 316,

PROVEN TECHNOLOGY

After more than 120 years of valve manufacturing, KLINGER Westad has designed a valve for special applications that will perform under extreme conditions.

Contact information

Contact us

Project sales: sales@klinger-westad.com

Spare parts: spareparts@klinger-westad.com

Service: service@klinger-westad.com

www.klinger-westad.com

KLINGER Westad
Heggenveien 530,
3360 Geithus, Norway
Tel: +47 32 78 95 00
sales@klinger-westad.com

Version 01. 2026